

RJS020



ULTRABOOST 1000A LITHIUM JUMP STARTER


The **ULTRABOOST 1000A** is capable of jump-starting vehicles with up to **5L Petrol and 2L Diesel engines**. Suitable for most 12V cars, vans, SUVs and LCVs.

The ULTRABOOST allows users to jump-start completely depleted batteries using the new boost button. The unique ergonomic smart clamp connection is equipped with longer cables to improve accessibility for harder to reach batteries. Ringtelligence technology for safer vehicle maintenance is included in the design of the clamps, offering reverse polarity protection, anti-spike protection and short circuit protection.

The integrated torch illuminates the work area whilst the LED indicators clearly display the current battery level. The USB-C port with PD30W fast charge technology allows for fast recharging of the ULTRABOOST unit and high power delivery to recharge devices such as tablets and phones.

- **ULTRABOOST** enables users to safely start vehicles with completely depleted batteries
- Powerful delivery with Peak Amps of 1000A and 250A Starting Amps for engines up to 5L Petrol and 2L Diesel
- Ringtelligence keeps users safe with reverse polarity protection and spark-free design
- Suitable for START/STOP batteries
- Unique ergonomic smart clamp battery terminal for secure, safe connection and easy reach cables perfect for harder to reach batteries
- PD30W Technology enables rapid recharging and fast charging of devices such as tablets and phones
- USB-C to USB-C and USB-A to USB-C cable included
- Clear charge indicator display and LED torch for use in low light conditions
- Compact and lightweight making it easy to handle and store within the vehicle
- Anti-slip base to stop the unit sliding on the engine bay
- Protective storage case included



Ring Automotive Limited
 Gelderd Road, Leeds, LS12 6NA United Kingdom
 Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266
 Email: autosales@ringautomotive.com . www.ringautomotive.com
 /ringautomotive



Specifications

Product Code	RJS020
Lithium Battery Capacity	8,000mAh
Start Current: 200A	250A
Peak Current: 500A	1000A
USB-C (input/output)	PD30W
USB (output)	Quick Charge (5V/9V/12V)
Charging Time	2 Hours
Weight	1.02kg
Dimensions	L201 x W134 x D113mm
Quantity	4 x 1
Barcode	5055175252605

Ringtelligence
technology



In-built safety features to protect from accident or incorrect use, including:
Reverse polarity protection
Anti-spike protection
Short circuit protection

Authorised Representative:
OSRAM GmbH
 Nonnendammallee 44, 13629 Berlin, Germany
 Email: automotive-service@osram.com
 www.osram.com